

ICT RS-485/OSDP Access Control Cable (FT6 Rated)

Specifically designed for access control applications, this RS-485 cable includes 18 AWG conductors for power supply and a 24 AWG shielded, twisted pair and drain wire for data transmission. It is ideal for use with the Protege module network, ICT readers and OSDP readers. The cable boasts a highly robust FT6 fire and smoke rating, making it suitable for plenum installations.

Technical Specifications

Ordering Information	
RS-485/OSDP Access Control Cable (FT6 Rated), 1000ft box	ICT-RS485-FT6
Power Wires (18AWG)	
Colors	Red, Black
Conductor Material	TC
Conductor Construction	7 × 0.39mm (0.015")
Insulation Material	FEP
Insulation Diameter	1.8mm (0.071")
Insulation Thickness	0.30mm average, 0.25mm minimum (0.012" average, 0.010" minimum)
Data Wires (24AWG)	
Form	Shielded twisted pair
Colors	Yellow, Purple
Conductor Material	TC
Conductor Construction	7 x 0.20mm (0.0079")
Insulation Material	FEP
Insulation Diameter	1.95mm (0.077")
Insulation Thickness	0.65mm average, 0.55mm minimum (0.026" average, 0.022" minimum)
Shield Material	AL/PET
Drain Wire	
Drain Wire Material	TC
Drain Wire Construction	7 x 0.20mm (0.0079")
Jacket	
Jacket Color	White
Jacket Material	PVC
Jacket Diameter	5.8mm (0.23")
Jacket Thickness	0.40mm average, 0.35mm minimum (0.016" average, 0.014" minimum)
Electrical Characteristics	
Direct Current Resistance at 20°C	18AWG: $\leq 21.9\Omega/\text{km}$ 24AWG: $\leq 90.9\Omega/\text{km}$
Characteristic Impedance	120 Ω ± 15

Maximum Operating Voltage	300V
Operating Conditions	
Operating Temperature	-20° to 75°C (-4° to 167°F)
Dimensions	
Gross Weight	17.1kg (37.7 lb)
Regulatory Standards	
Communications Cable Standard	UL444
Fire and Smoke Ratings	CMP FT6

Designers & manufacturers of integrated electronic access control, security and automation products.
Designed & manufactured by Integrated Control Technology Ltd.
Copyright © Integrated Control Technology Limited 2003-2025. All rights reserved.

Disclaimer: Whilst every effort has been made to ensure accuracy in the representation of this product, neither Integrated Control Technology Ltd nor its employees shall be liable under any circumstances to any party in respect of decisions or actions they may make as a result of using this information. In accordance with the ICT policy of enhanced development, design and specifications are subject to change without notice.